




## Green Pin® Needle Bearing Swivel EE GR8

### Grade 8 needle bearing eye-eye swivel



ELR



- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MTC®
- **Note:** equipped with two needle roller thrust bearings to enable rotation under load

for chain diameter		working load limit	diameter	length outside	width outside	length inside	width inside	length	thickness	weight each
mm	inch	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
5-6	<sup>3</sup> / <sub>16</sub> - <sup>7</sup> / <sub>32</sub>	1.12	11	150	56	33	32	126	6	0.61
7-8	<sup>1</sup> / <sub>4</sub> - <sup>5</sup> / <sub>16</sub>	2	14	181	65	40	37	153	8	1.07
10	<sup>3</sup> / <sub>8</sub>	3.2	18	226	79	47	48	195	11	1.9
13	<sup>1</sup> / <sub>2</sub>	5.4	20	268	96	59	58	227	14	3.17
16	<sup>5</sup> / <sub>8</sub>	8.2	23	331	121	67	73	281	17	6.44
18-20	<sup>3</sup> / <sub>4</sub>	12.8	28	378	132	88	82	328	22	7.75