



- Manufactured from forged alloy steel, quenched and tempered.
- Manufactured and tested in accordance with EN1677-1.
- Certified by DGUV GS-OA-15-03.
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts are traceable to Test Certification.
- Proof tested to 2.5 times the WLL.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.
- WLL forged onto each product for quick and easy identification.
- Lugs designed to assist the welding process.

Excavator Hook

Metric (8-083)

Item No.	Working Load Limit tonnes	Dimensions (mm)								N.W. kg
		F	H	L	P	T	W	HV	a	
8-083-0075	0.75	19	20	56	19	13	81.5	5	3	0.3
8-083-01	1.0	25	27	72	27	17	95	6	4	0.6
8-083-02	2.0	30	30	86	33	20	114	8	5	0.9
8-083-03	3.0	35	32	105	30	23	132	10	6	1.4
8-083-04	4.0	42	38	114	30	29	140	11	7	1.9
8-083-05	5.0	45	47	131	32	30	165	12	8	2.9
8-083-08	8.0	50	51	133	34	40	172	13	9	3.5
8-083-10	10.0	55	61	170	51	43	220	14	9	6.3
8-083-15	15.0	60	67	184	53	50	240	15	12	8.8

* Design factor 5:1

YOKE recommends that the working load limit should be reduced to meet any appropriate legislative requirements, if welding on to an excavator. Please contact your YOKE distributors for further information.

Excavator Hook

Imperial (8-083)

Item No.	Working Load Limit tonnes	Dimensions (inch)								N.W. lbs
		F	H	L	P	T	W	HV	a	
8-083-0075	0.75	0.75	0.79	2.20	0.75	0.51	3.21	0.20	0.12	0.6
8-083-01	1.0	0.98	1.06	2.83	1.06	0.67	3.74	0.24	0.16	1.2
8-083-02	2.0	1.18	1.18	3.39	1.30	0.79	4.49	0.31	0.20	2.0
8-083-03	3.0	1.38	1.26	4.13	1.18	0.91	5.20	0.39	0.24	3.1
8-083-04	4.0	1.65	1.50	4.49	1.18	1.14	5.51	0.43	0.28	4.3
8-083-05	5.0	1.77	1.85	5.16	1.26	1.18	6.50	0.47	0.31	6.3
8-083-08	8.0	1.97	2.01	5.24	1.34	1.57	6.77	0.51	0.35	7.7
8-083-10	10.0	2.17	2.40	6.69	2.01	1.69	8.66	0.55	0.35	14.0
8-083-15	15.0	2.36	2.64	7.40	2.09	1.97	9.45	0.59	0.47	19.3