



- Quenched and Tempered Alloy Steel.
- At least 25% greater WLL than traditional G80 products.
- Manufactured in accordance with EN 1677- 3 and ASME B30.26, ASME B30.10, PAS1061.
- Certified by DGUV GS-OA-15-05 & DGUV GS-MO-15-05.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Design Factor 4:1.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Tempering temperature minimum 400°C
- Magnaflux crack detection is performed 100% on each batch.



**8-P025T**

For trigger

## G-100 Swivel Self Locking Hook

With Brass Bushing

Item No.	For Grade 100 Chain	WLL tonnes*	Dimensions (mm)							N.W. kg
	mm		A	B	D	H	K	P	T	
X-027-06	6	1.4	32	22	12	19	149	28	15	0.7
X-027-07	7,8	2.5	36	29	13	24	186	34	20	1.2
X-027-10	10	4.0	41	34	16	30	218	44	26	2.0
X-027-13	13	6.7	46	43	21	39	276	51	30	4.1
X-027-16	16	10.0	61	50	23	49	329	60	36	7.2
X-027-20	20	16.0	74	82	25	65	387	70	53	13.0
X-027-22	22	19.0	97	95	33	63	457	80	49	20.0
X-027-26	26	26.5	123	115	42	69	535	99	56	33.0

★ Design factor 4:1 proof tested and certified.